



## FIRE EXTINGUISHING PANEL TYPE : FS5200E



### TECHNICAL DATA

System	: Conventional
Fire Alarm Lines	: 3 (2 for extinguishing control & 1 for fire detection)
Max No of detectors	: 32 per line
Controllable inputs for	: Manual extinguishing activation (1), Extinguishing keeping (1), Extinguishing disable (1), Mode selection (1), Monitoring the extinguishing outflow (1)
Controllable outputs relay 24VDC for	: Sounders in fire condition (1), Sounders in extinguishing status (1), Extinguishing switching on (1)
Relay outputs switching 3A/125VAC, 3A/30VDC) for	: Fire condition (3), Extinguishing (3), Fault condition (3)
Power supply	: 220/230VAC, 50/60Hz
Backup battery	: 2 X 12V/12Ah
Maximum current to external	: 2,5A at 24VDC
Operating temperature range	: -5°C to +40°C
Relative humidity resistance	: (93±3)% at 40°C
Dimensions	: 450mmX355mmX115mm
Weight	: 6,6kgr (excluding the backup battery)
Manufacturer	: UNIPOS Ltd
Origin	: European Union
Certificates	: EN54-2:1997/A1:2006/AC:2009, EN54-4:1997/A2:2006/AC:2009, EN12094-1:2003